

THERMAL TRANSFER OVERPRINTERS SVM TR53 SVM TR107



SPECIFICATIONS

High performance, low cost Traverse thermal transfer printers are versatile enough for printing fixed and variable text, data and graphics. It is ideal for reproducing bar codes, real time, sell-by dates, batch numbers, prices, source codes and much more.

KEY FEATURES

- Patented long life mechanical design needs no maintenance
 - 53mm x 410mm and 107mm x 410mm print area
 - 600m ribbon capacity
 - Print Quality 300dpi (12 dot / inch).
- The USB can be used to:
 - Move messages and configurations between printers for local based set-up
 - Back-up and restore messages and printer settings
- Large memory for all label formats to be stored locally.

Savema

Marking and Coding Machines
www.savema.com.tr

SVM TR53 // SVM TR107

Specifications

	TR53	TR107
Print Area	Width 53mm Length 410mm	Width 107mm Length 410mm
Resolution	12 dots/mm (300dpi) horizontally and vertically	
Print Speed	Up to 400mm / second	
Production	-	
Thermal Ribbon	600 meter (656 yds.) loaded ribbon	
Memory	5000 text memory, 512 Mb. Ram, 1 Gb Storage (Onboard), Up to 8 Gb SD Memory Support, Up to 16 Gb USB Memory Support	
Power Supply	110/220/240 V 50/60 Hz	
Air Supply	min. 1 bar - max. 6 bar	
Wight (printer)	23 kg	
Dimensions	238mm H x 312mm W x 700mm D 238mm H x 370mm W x 700mm D	
Outputs	Machine on error (failsafe) - image ready, power on, print per minute etc	
Ribbon Widths	55 mm and 110 mm. (2,2" - 4,28")	
Operating Temperature	5° - 50°C (41° - 104°F)	
Control Panel	7" Touch Screen Panel	

Programming

Fields	Real DATE/Time. Text, Barcode, 2D Barcodes, Logo, Counter (Serial No), Shift Code, Shape, Currency
Barcodes	1 D Barcodes (EAN-13,EAN-8,CODE 128, CODE 39, ITF -2of 5,ITF 14, CODABAR UPC-A,UPC-E) 2 D Barcodes (Datamatrix, QR Codes. PDF 41 7, Aztec code.Semacode, Macro PDF 417) ITF14, RSS (GS-1 DATABAR COMPOSITE)
Communications	RS-232 (PC), LAN, USB Multi-language (14) support standard
Pc Programmes	SAYASIS Label Program

